

## 8 Wireless + Wired Zones Alarm System



Supplying power:	DC4.8~16V
Static current:	25mA
Power:	< 1W
Siren alarm output:	> 400mA, DC12V
Wireless frequency:	315 MHz
Weight:	0.8 kg
Size:	160x115x35mm



**Power Supply**    **Remote**    **Wireless Magnetic**    **Wireless PIR**    **Wired Siren**

### Specifications

The system has **8 wireless zones + 7 wired zones with build in keypad**, LED indications make it easy to learn more message. It adopted MCU technology with good quality and flexible wiring ports, high digital communicate mode, and handshake frequency. The system can program many items: the alarming voice, the zone attribute, and telephone numbers.

Set up to four alarming telephone numbers to 12 digits. When alarm is triggered, the system will dial the stored number one by one circularly. Can easily use telephone to listen in, to arm and disarm the unit. The system also has built-in voice module which can record 10 seconds voice so that can make voice alarming. Have a backup battery which continues to work for 24 hours.

**5 Arm Status:** out arm, home arm, single zone arm, delay arm, and remote control arm.

**5 Zone Attributes:** instant, delay, emergency, inner, and stay zone.

### SpyNet

Rukan Grand Panglima Polim No. 89

Jl. Panglima Polim Raya, Kebayoran Baru, Jakarta Selatan 12160 Indonesia

Tel: (021) 726 3022 (hunting)    Fax: (021) 726 3005    Web: [www.spynet.co.id](http://www.spynet.co.id)

DAFTAR PERALATAN ALARM WIRELESS

No.	Item No.	Item Name	Description	Picture
1	HW-01A	Wireless P.I.R Detector	Power DC9V dry battery - Battery life: about half year - Detect Area: Vertically: 60°, Horizontally: 110°	A white, rectangular wireless PIR detector with a small antenna on top.
2	HW-XD01	Wireless PIR Ceiling Detector	Power DC3VCR123A battery Working temperature:-5 °C-55 °C Static current: <20HA Alarm current: <15mA Anti-electromagnetism : >30 v/m Anti-white-light : >6500 LUX Detecting angle: 360° Place of installation: 2.4 m	A circular, white ceiling-mounted PIR detector.
3	HW-04A	wireless PIR sensor with pet immune	Effectively prevent the pet interference. Use of advanced non-linear filtering technology, a powerful anti-light function and anti-capacity rate of false positives.	A white, rectangular wireless PIR sensor with a small antenna on top.
4	MC-01	Wireless Door/window Gap Detector	Power DC9V battery -315MHz Gap for triggered, >15-20mm Stand-by current: 0.01W Alarm current: 0.09W	A white, rectangular wireless door/window gap detector with a small antenna on top.
5	SW-01	Wireless Water Level Detector	Ceiling Installation and lateral installation	A white, rectangular wireless water level detector with a small antenna on top.
6	YG-01	Wireless Smoke Alarm	Power DC9V battery - 315MHz Alarm current: <25 mA Static current: <20 uA Alarm volume: >95db Relative humidity: >85 %	A circular, white ceiling-mounted smoke alarm.
7	QG-01	Wireless Gas Detector/Alarm	Power supply: AC110-240V - 315MHz Alarm limit: Coal gas 2000ppm ± 30%; Solid petroleum 5000 ppm ± 30% ( LPG ); Natural gas 2000 ppm ±30 Insulation: Insulation resistance > 50	A white, rectangular wireless gas detector with a small antenna on top.
8	JA-01	Wireless Panic Button	Emergency help for elder patients; Control distance: < 80m(outdoor)	A small, square, light green panic button with a red circular button in the center.
9	JA-02	Wristwatch Style Panic Button	<b>Emergency help for elder patients;</b> Control distance: < 40m(outdoor)	A wristwatch-style panic button with a red circular button on the face.
10	FD-01	Signal Repeater (match adaptor)	Signal tranfer, extend the distance between wireless sensors with control panel ; remote arm/disarm, wireless signal transfer within 200 m to 500 m	A white, rectangular signal repeater with a small antenna on top.
11	LB-W03	Wireless outdoor siren with flash (match adaptor)	Alarm sounds over 120 dB, also with a bright flash when alarming	A white, rectangular outdoor siren with a red lens.